

# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER : 02178339  
PUBLICATION DATE : 11-07-90

APPLICATION DATE : 29-12-88  
APPLICATION NUMBER : 63335036

APPLICANT : MITSUI PETROCHEM IND LTD;

INVENTOR : ASO HIROTAKE;

INT.CL. : C08L 23/04 C08L 23/10 //(C08L 23/04 , C08L 81:02 ), (C08L 23/10 , C08L 81:02 )

TITLE : HEAT RESISTANT POLYOLEFIN RESIN COMPOSITION AND RESIN MOLDED ARTICLE

ABSTRACT : PURPOSE: To obtain a heat resistant polyolefin resin composition capable of providing a molded article having excellent thermal aging properties and heat resistant stiffness by blending a polyolefin composed mainly of ethylene or propylene with polyphenylene sulfide at a specific ratio.

CONSTITUTION: The composition consisting essentially of (A) 40-78wt.%, preferably 60-78wt.% polyolefin composed mainly of ethylene or propylene, preferably low-density polyethylene having 3-20g MFR and 0.915-0.93g/cm<sup>3</sup> density, graft- modified polyolefin having 0.6-10dl/g intrinsic viscosity and  $\geq 130^{\circ}\text{C}$  melting point and grafted by 0.1-5wt.% unsaturated carboxylic acid (derivative) and (B) 22-60wt.%, preferably 22-40wt.% polyphenylene sulfide, preferably having 50-50000 poise melt viscosity. The molded article obtained by subjecting the above-mentioned composition to injection molding and having the component B forming a laminar continuous phase in the surface layer part.

COPYRIGHT: (C)1990,JPO&Japio